



## 1560 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### CONFIGURATIONS



**1560**  
Standard



**1564**  
With Padded Dividers



**1560NF**  
No Foam




**1560TP**  
With TrekPak Divider System



**1560WF**  
With Foam



**1560TPL**  
TrekPak Divider System with  
Mesh Lid Organizer



**1560PDL**  
Padded Dividers with Mesh Lid  
Organizer

### DIMENSIONS

<b>Interior (L×W×D)</b>	19.92 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm)
<b>Exterior (L×W×D)</b>	22.07 x 17.92" x 10.42 (56.1 x 45.5 x 26.5 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	7.00" (17.8 cm)
<b>Total Depth</b>	9" (22.9 cm)
<b>Int Volume</b>	1.55 ft³ (0.044 m³)
<b>Padlock Hole Diameter</b>	0.31" (0.8 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

COLOURS

 Black	 Desert Tan	 Orange	 Yellow
---	--	--	--

WEIGHT

<b>Weight With Foam</b>	20.00 lbs (9.07 kg)
<b>Weight Empty</b>	17.00 lbs (7.71 kg)
<b>Buoyancy</b>	115.00 lbs (52.16 kg)
<b>Master Pack Weight</b>	21.00 lbs (9.53 kg)

TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	190°F (87.8 °C)

CERTIFICATIONS

<b>IP67</b>
<b>Def Stan 81-41</b>

OTHER

<b>Wheels</b>	2
<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Nameplate</b>	yes
<b>Military</b>	yes

ACCESSORIES

				
<b>0343</b> Replacement O-ring	<b>1561</b> 4 pc. Replacement Foam Set	<b>1565</b> Padded Divider Set	<b>1569</b> Lid Organizer	<b>1560EUTP</b> TrekPak Case Divider Kit
				
<b>1560TPKIT</b> TrekPak Case Divider Kit	<b>1560TPDIV</b> Extra TrekPak Dividers	<b>1507</b> Quick Mounts - set of 4	<b>1506TSA</b> TSA Lock	<b>1500D</b> Desiccant Silica Gel



**1560MP**  
EZ-Click™ MOLLE Panel

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 01-31-26*