

1560 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

• Strong polyurethane wheels with stainless steel bearings

- Watertight, crushproof, and dustproof
- 2 level Pick N Pluck[™] with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS







1560TP With TrekPak Divider System

1560WF With Foam

 1560TPL
 1560PDL

 TrekPak Divider System with Mesh Lid Organizer
 Padded Dividers with Mesh Lid Organizer



DIMENSIONS

| 2 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm) |
|--------------------------------------------|
| 7 x 17.92" x 10.42 (56.1 x 45.5 x 26.5 cm) |
| " (5.1 cm) |
| " (17.8 cm) |
| 2.9 cm) |
| ft³ (0.044 m³) |
| " (0.8 cm) |
| |

MATERIALS

| Polypropylene |
|--------------------------------|
| ABS |
| Polymer |
| Stainless Steel |
| 1.3 lb Polyurethane |
| ABS |
| 3 Micron Hydrophobic Non-Woven |
| |

COLOURS

| Black | Desert Tan | Orange | Yellow | |
|-------|------------|--------|--------|--|
| | | | | |

WEIGHT

| Weight With Foam | 20.00 lbs (9.1 kg) |
|--------------------|----------------------|
| Weight Empty | 17.00 lbs (7.7 kg) |
| Buoyancy | 115.00 lbs (52.2 kg) |
| Master Pack Weight | 21.00 lbs (9.5 kg) |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) |
|---------------------|-----------------|
| Maximum Temperature | 190°F (87.8 °C) |

CERTIFICATIONS

| IP67 | |
|----------------|--|
| Def Stan 81-41 | |

OTHER

| Wheels | 2 |
|-------------------|-----|
| Extendable Handle | yes |
| Master Pack | 1 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES



0343 Replacement O-ring



1560TPKIT TrekPak Case Divider Kit



1561 4 pc. Replacement Foam Set

1560TPDIV

Extra TrekPak Dividers





1507 Quick Mounts - set of 4



1569 Lid Organizer



1506TSA TSA Lock



1560EUTP TrekPak Case Divider Kit



1500D Desiccant Silica Gel





1560MP EZ-Click™ MOLLE Panel

 Peli

 c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

 info@peli.com

 • www.peli.com

Document created on 09-09-25