



# 1510M

## Protector

### Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings**

- **The Mobility Version of the 1510 Case is over the maximum FAA carry on size**

- **Water resistant, crushproof, and dust resistant**

- Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded top and side handles

- Easy open double-throw latches

- O-ring seal

- Open cell core with solid wall design - strong, light weight

- Retractable extension trolley handle

- Stainless steel hardware and padlock protectors

- Peli's legendary lifetime guarantee\*\*

- \* Check with your airline for exact measurement requirements.

- \* Where applicable by law



## CONFIGURATIONS



**1510M**  
Standard



**1510MNF**  
No Foam



**1510MWF**  
With Foam

## DIMENSIONS

<b>Interior (LxWxD)</b>	19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm)
<b>Exterior (LxWxD)</b>	23.55 x 14.36" x 10.62 (59.8 x 36.5 x 27 cm)
<b>Lid Depth</b>	1.79" (4.5 cm)

<b>Bottom Depth</b>	5.79" (14.7 cm)
<b>Total Depth</b>	7.58" (19.3 cm)
<b>Int Volume</b>	0.96 ft <sup>3</sup> (0.027 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

COLOURS

 Black

WEIGHT

<b>Weight With Foam</b>	17.91 lbs (8.1 kg)
<b>Weight Empty</b>	16.30 lbs (7.4 kg)

TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	190°F (87.8 °C)

CERTIFICATIONS

**IP57**

OTHER

<b>Wheels</b>	2
<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Nameplate</b>	yes
<b>Reduced Area</b>	yes
<b>Military</b>	yes

ACCESSORIES



**1511**  
 4 pc. Replacement Foam Set



**1513**  
 Replacement O-ring



**1515**  
 Padded Divider Set



**1519**  
 Lid Organizer



**1507**  
 Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**1510TPKIT**  
TrekPak Case Divider Kit



**1510TPDIV**  
Extra TrekPak Dividers

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 09-16-25*