



## 2460Z1 StealthLite™

The rechargeable version of the StealthLite™ 2410 LED. The StealthLite™ Rechargeable 2460Z1 LED uses the 2469P NiMH battery and comes with the charger base unit cat # 2480F that can be installed at home or work using the 220V transformer cat # 2468Z1. Certified to ATEX Zone 1 (Category 2). Note, this charger base does not work on 12v systems.



### DIMENSIONS

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 7.00" (17.8 cm) |
|---------------|-----------------|

### MATERIALS

|                                |                                    |
|--------------------------------|------------------------------------|
| <b>Body</b>                    | Anti-static Impact Modified PC/PBT |
| <b>O-Ring</b>                  | Ethylene Propylene                 |
| <b>Lens</b>                    | Polycarbonate (PC)                 |
| <b>Shroud</b>                  | Anti-static Impact Modified PC/PBT |
| <b>Contact Spring Retainer</b> | Stainless Steel / Phosphore Bronze |

### COLOURS

|                                                                                                            |
|------------------------------------------------------------------------------------------------------------|
|  High Visibility Yellow |
|------------------------------------------------------------------------------------------------------------|

### LIGHT SPECS

|                  |     |
|------------------|-----|
| <b>Lamp Type</b> | LED |
|------------------|-----|

### POWER

|                           |       |
|---------------------------|-------|
| <b>Battery Size</b>       | AA    |
| <b>Battery Type</b>       | NiMH  |
| <b>Battery Quantity</b>   | 4     |
| <b>Batteries Included</b> | yes   |
| <b>Rechargeable</b>       | yes   |
| <b>Charge Time</b>        | 5 hrs |
| <b>Volts</b>              | 4.8v  |

### WEIGHT

|                                 |                 |
|---------------------------------|-----------------|
| <b>Weight With Batteries</b>    | 7.8 oz (221 gr) |
| <b>Weight Without Batteries</b> | 4.4 oz (125 gr) |
| <b>Packaged Weight</b>          | 1.4 oz (40 gr)  |

### SWITCH

|                    |                          |
|--------------------|--------------------------|
| <b>Switch Type</b> | One-handed Safety Switch |
| <b>Light Modes</b> | On / Off                 |

CERTIFICATIONS

|             |  |
|-------------|--|
| ATEX Zone 1 |  |
| OTHER       |  |

|              |     |
|--------------|-----|
| Minimum Pack | 1   |
| Military     | yes |
| Package Code | C   |

| FL1 STANDARD                                                                        | HIGH       |
|-------------------------------------------------------------------------------------|------------|
|    | 181 LUMENS |
|    | 5h 0mins   |
|   | 181m       |
|  | 8235cd     |
|  | IPX7       |

ACCESSORIES



**0770**  
Helmet Light Holder



**2480F**  
Deck/Dash Charger Base Unit



**2469P**  
Replacement Battery

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 05-09-24*