



## 472-PWC-DW3300

### Waffenbehälter

FieldPak

The DW3300 FieldPak from Peli-Hardigg™ combines a softshell padded rifle case with our toughest hardshell protective case for the best of both worlds. In the field, the softshell padded case is lightweight and maneuverable enough to get you into position quickly. On the move, the padlockable hardshell case backs it up with impact, temperature, and moisture resistance for total protection. Together, they offer the most security possible for your weapon. Don't go halfway when it comes to protecting your weapon - go double duty.

472-DW3300 soft rifle bag holds up to 2 rifles.


- Two (2) MOLLE adapter panels with Velcro on back and MOLLE straps on front.
- Two (2) zippered pouches with Velcro on back and MOLLE straps on front 8"L 7"W x 3.25"D
- Six (6) Velcro straps to hold weapons and accessories in place
- Two (2) Velcro backed 1.5" wide x 12" long Muzzle covers, fits SIG XM7 fixed suppressor
- One (1) 8" long fabric carry handle
- One (1) padded back strap set for backpack style carry.
- Fits in Peli™ Storm Case™ iM3300
- NSN Numbers: DW3300 8135-01-564-8874 (Black), 8135-01-564-8875 (Coyote)
- Beschränkte lebenslange Garantie von Peli\*
- \*Die lebenslange Garantie gilt nicht, wo dies gesetzlich unzulässig ist




## KONFIGURATIONEN




**472-PWC-DW3300**  
Standard




**472-PWC-DW3300-BLK-BLK**  
Black Case With Black Soft Case



**472-PWC-DW3300-BLK-COY**  
Black Case With Coyote Soft Case



**472-PWC-DW3300-OD-BLK**  
Green Case With Black Soft Case



**472-PWC-DW3300-OD-COY**  
Green Case With Coyote Soft Case

## GRÖSSE

<b>INNERE</b>	50.50 x 14.00" x 6.00 (128.3 x 35.6 x 15.2 cm)
<b>AUSSEN</b>	53.80 x 16.50" x 6.70 (136.7 x 41.9 x 17 cm)
<b>Deckeltiefe</b>	2.00" (5.1 cm)
<b>Bodentiefe</b>	4.00" (10.2 cm)
<b>Gesamttiefe</b>	6" (15.2 cm)
<b>Innenvolumen</b>	2.45 ft <sup>3</sup> (0.069 m <sup>3</sup> )

## MATERIALEN

<b>Gehäuse</b>	Injection Molded HPX™ high performance resin
<b>Verschluss</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Verschluss (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring Dichtung</b>	Silicone Sponge

<b>Stifte</b>	Stainless Steel
<b>Schaumstoff</b>	1.3/1.35 polyester
<b>Ausgleichsschraube</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Ausgleichsschraube (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Ausgleichsventil</b>	Gortex membrane

## FARBEN

---

■ Black	■ OD Green
---------	------------

## GEWICHT

---

<b>Gewicht</b>	23.00 lbs (10.43 kg)
----------------	----------------------

## TEMPERATUR

---

<b>min. Temperatur</b>	-20°F (-28.9 °C)
<b>max. Temperatur</b>	140°F (60 °C)

## ANDERE

---

<b>Laufrollen</b>	2
-------------------	---

---

### **Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 06-09-26*