# 9490



Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply
- Up to 6,000 lumens (calculated)
- Up to 24 hrs of run time
- Intelligent Control (allows for various light output levels)

## DIMENSIONS

| | |
|---|---|
| **Head (L×W×D)** | 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm) |
| **Closed (L×W×D)** | 20.00 x 6.50" x 11.25 (50.8 x 16.5 x 28.6 cm) |
| **Light Head Height (max)** | 72.00" (182.9 cm) |

## MATERIALS

**Body** Polypropylene
**Head** Aluminum
**Mast** Aluminum
**Lens** Polycarbonate (PC)

## COLOURS

Black Yellow

## LIGHT SPECS

| | |
|---|---|
| **Lumens (High)** | 6000 |
| **Lamp Heads** | 1 |
| **Lamp Type** | LED |
| **Number of LEDs** | 10 |
| **Beam Spread** | 125° |
| **IP Rating** | 54 |

## POWER

| | |
|---|---|
| **Run Time (High)** | 3.50 hrs |
| **Run Time (Med)** | 12.00 hrs |
| **Run Time (Low)** | 24.00 hrs |
| **Battery Type** | Sealed Lead Acid (SLA) |
| **Rechargeable** | yes |
| **Battery Lifespan** | 500 cycles |
| **Charge Time** | 8 hrs |
| **Battery Level Indicator** | Full-time battery level display and low battery warning (visible flashing) |
| **Sockets (Primary)** | 1 |
| **Volts** | 12.0v |

## WEIGHT

**Weight** 32.00 lbs (14.51 kg)

## SWITCH

| | |
|---|---|
| **Switch Type** | Silicone Rubber Keypad |
| **Light Modes** | High / Medium / Low / Flashing |

## ACCESSORIES



**9483**
Power Supply




**9487**
Padded Shoulder Strap



**9489**
Powerpack



**9447**
DC Vehicle Charger Cord

**Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

*Document created on 11-10-26*