

1556

Air

Peli understands that finding the right protection, with the perfect fit for your gear, is a priority. Peli™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Peli's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Peli's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Peli has you covered.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- · Business card holder
- Maximum airline carry-on size*
- Press and Pull™ Latches
- · Limited Lifetime Warranty
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- · Waterproof O-ring seal
- User-customizable Pick N Pluck[™] foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1556 Standard



1556WF With Foam



1556NF No Foam

DIMENSIONS

Interior (L×W×D) 21.63 x 10.76" x 8.97 (54.9 x 27.3 x 22.8 cm) Exterior (L×W×D) 23.43 x 13.52" x 10.57 (59.5 x 34.3 x 26.8 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 6.97" (17.7 cm)

 Total Depth
 8.97" (22.8 cm)

 Int Volume
 1.21 ft³ (0.034 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS O-Ring EPDM

Purge Body ABS

Purge Vent Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

 Weight With Foam
 11.20 lbs (5.1 kg)


 Weight Empty
 9.75 lbs (4.4 kg)

 Buoyancy
 84.95 lbs (38.5 kg)

TEMPERATURE

Minimum Temperature 0°F (-17.8 °C) **Maximum Temperature** 140°F (60 °C)

ACCESSORIES



1556AirFS 7 pc. Replacement Foam Set



1506TSA TSA Lock



RucPac-Pro-1 RucPac Pro Hardcase Backpack Conversion



AIRHANDL EZ-Pull Multi-Stage Air Handle

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 11-05-25