

1630

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

• 4 strong polyurethane wheels with stainless steel bearings (wheel diameter is 5.3cm)

- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck™ with convoluted lid foam
 Automatic pressure equalization valve balances interior pressure, keeps
- · Easy open double-throw latches
- Fold down handles
- Note: Please consult a sales specialist for more details.
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Reinforced corners
- Retractable extension trolley handle
- Stackable
- Stainless steel padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1630 Standard



1634 With Padded Dividers



1630NF No Foam



1630WF With Foam

DIMENSIONS

Interior (L×W×D) 27.70 x 20.98" x 15.50 (70.4 x 53.3 x 39.4 cm) Exterior (L×W×D) 31.28 x 24.21" x 17.48 (79.5 x 61.5 x 44.4 cm)

Lid Depth 3.25" (8.3 cm) **Bottom Depth** 12.14" (30.8 cm) **Total Depth** 15.39" (39.1 cm) **Int Volume** 5.21 ft³ (0.148 m³) Padlock Hole Diameter 0.31" (0.8 cm)

MATERIALS

Body

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 36.00 lbs (16.3 kg)

 Weight Empty
 31.00 lbs (14.1 kg)

 Buoyancy
 350.00 lbs (158.8 kg)

 Master Pack Weight
 42.00 lbs (19.1 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels 4
Extendable Handle yes
Master Pack 1
Nameplate yes
Reduced Area yes

ACCESSORIES



1631 5 pc. Replacement Foam Set



1633 Replacement O-ring



1635 Padded Divider Set



1639 Lid Organizer



1630DCDocument Container
Accessory



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 09-13-25