1525
Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 45 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.
With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.



- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified

CONFIGURATIONS



1525
Standard



1525NF
No Foam



1525WD
With Padded Dividers



1525TP
With TrekPak Divider System



1525WF
With Foam



WHISKEY-1B
Single Bottle Whiskey



WHISKEY-2B
2 Bottle Whiskey

DIMENSIONS

Interior (L×W×D)	20.50 x 11.31" x 6.75 (52.1 x 28.7 x 17.1 cm)
Exterior (L×W×D)	21.96 x 13.97" x 7.49 (55.8 x 35.5 x 19 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	4.75" (12.1 cm)
Total Depth	6.75" (17.1 cm)
Int Volume	0.91 ft³ (0.026 m³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS

Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black | Orange | Silver | Yellow

WEIGHT

Weight With Foam	7.13 lbs (3.23 kg)
Weight Empty	5.99 lbs (2.72 kg)
Buoyancy	57.90 lbs (26.26 kg)

TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)


ACCESSORIES



1525AirFS
3 pc. Replacement Foam Set



1525AirDS
Padded Divider Set



1525TP-KIT
TrekPak Case Divider Kit



1525TPKIT
TrekPak Case Divider Kit



1525TPDIV
Extra TrekPak Dividers



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



RucPac-Pro-1
RucPac Pro Hardcase
Backpack Conversion

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 11-22-26