



1605

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 40 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Fold down overmolded handle
- Stainless steel padlock protectors
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1605
Standard



1605NF
No Foam



1605WD
With Padded Dividers



1605TP
With TrekPak Divider System



1605WF
With Foam

DIMENSIONS

Interior (LxWxD)	26.00 x 14.00" x 8.38 (66 x 35.6 x 21.3 cm)
Exterior (LxWxD)	28.87 x 16.77" x 9.12 (73.3 x 42.6 x 23.2 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	6.38" (16.2 cm)
Total Depth	8.38" (21.3 cm)
Int Volume	1.77 ft ³ (0.05 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

■ Orange

■ Silver

■ Yellow


WEIGHT

Weight With Foam 11.61 lbs (5.3 kg)
Weight Empty 9.28 lbs (4.2 kg)
Buoyancy 112.90 lbs (51.2 kg)

TEMPERATURE

Minimum Temperature -60°F (-51.1 °C)
Maximum Temperature 160°F (71.1 °C)

ACCESSORIES



1605TP-KIT
TrekPak Case Divider Kit



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 08-18-22