



1500EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open Double Throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

Interior (LxWxD)	16.84 x 11.27" x 6.09 (42.8 x 28.6 x 15.5 cm)
Exterior (LxWxD)	18.54 x 14.05" x 6.89 (47.1 x 35.7 x 17.5 cm)
Lid Depth	1.81" (4.6 cm)
Bottom Depth	4.31" (10.9 cm)
Total Depth	6.12" (15.5 cm)
Int Volume	0.67 ft ³ (0.019 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black	Desert Tan	Orange	OD Green
Silver	Yellow		

WEIGHT

Weight With Foam	7.94 lbs (3.6 kg)
Weight Empty	7.13 lbs (3.2 kg)
Buoyancy	50.00 lbs (22.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41
STANAG 4280
ATA 300

OTHER

Master Pack 4
Nameplate yes
Military yes

ACCESSORIES



1501
3 pc. Replacement Foam Set



1503
Replacement O-ring



1505
Padded Divider Set



1508
Photographer's Lid Organizer



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1505EMS
EMS Accessory Set (Lid Organizer and Divider Set)

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-12-21