# PR2015-01/18/01

## ProRack™

8U



Peli™ ProRack™ cases are lightweight, space-efficient, front and rear opening transport container (not a shock mounted/cushioned rackmount system) for field ruggedized equipment.

• Designed for equipment up to 75 lbs
• Equipment typically will have 80-120 G fragility
• Rugged 18" deep cases w/ aircraft aluminum frame suspended on plastic fins to protect your gear from direct impact transmission
• Often used for field-deployed amplifiers and electronic, medical or testing equipment components

## DIMENSIONS

| | |
|---|---|
| **Exterior (L×W×D)** | 22.00 x 22.40" x 18.30 (55.9 x 56.9 x 46.5 cm) |
| **Rack Depth** | 18.00" (45.7 cm) |
| **Interior Lid Depth** | 1.81" (4.6 cm) |
| **Interior Back Lid Depth** | 1.81" (4.6 cm) |

## MATERIALS

## COLOURS

Black - 032 Fed Std 27040

## WEIGHT

| | |
|---|---|
| **Weight** | 27.30 lbs (12.4 kg) |

**Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

*Document created on 03-28-24*