

9440

NOW TWICE AS BRIGHT

The 9440 now offers three pre-set power levels, battery level indication and comes equipped with a lithium ion rechargeable battery. The 9440 moves fast to light up ravines, confined spaces, riverbanks, anyplace generator lights can't go. Deployed, the mast extends 7 feet (2.1 meters) high, shining light over low obstructions encountered by traditional lantern style lights. With a 125 degree beam spread and up to 5300 lumens, your entire work area will have the light you need for a safe and efficient operation. The 9440 is able to run directly from wall power if needed and can be left on charge indefinitely which makes for an invaluable emergency preparedness tool.

The 9440 is maintenance free, using super tough LED lamp modules and a lithium ion battery for up to 8 hours of continuous light.

Adjustable carrying strap included.

- Built Peli tough
- Convenient shoulder strap
- RoHS and CE Compliant
- Equipped with a lithium ion rechargeable battery
- Mast extends 7 feet (2.1 meters) high when deployed
- Up to 5300 lumens
- Up to 8 hours run time

DIMENSIONS

Head (L×W×D)	7.87 x 7.87" x 3.50 (20 x 20 x 8.9 cm)
Closed (L×W×D)	37.40 x 7.87" x 7.87 (95 x 20 x 20 cm)
Full (L×W×D)	85.00 x 35.83" x 35.83 (215.9 x 91 x 91 cm)
Light Head Height (max)	85.00" (215.9 cm)

MATERIALS

Body	Polypropylene
Head	Polycarbonate (PC) / ABS
Mast	Aluminum
Lens	Polycarbonate (PC)

COLOURS

Black

Yellow

LIGHT SPECS

Lumens (High)	5300	
Lumens (Med)	2800	
Lumens (Low)	1400	
Lamp Heads	1	
Lamp Type	LED	
Number of LEDs	12	
Beam Spread	125°	
IP Rating	65	



POWER

Run Time (High)	1.50 hrs
Run Time (Med)	4.00 hrs
Run Time (Low)	8.00 hrs
Battery Type	Lithium-Ion
Rechargeable	yes
Battery Lifespan	500 cycles
Charge Time	3 hrs 45 mins
Battery Level Indicator	Level indicator
Sockets (Primary)	1
Volts	14.4v

WEIGHT

Weight	16.09 lbs (7.3 kg)	
SWITCH		
Switch Type	Silicone Rubber Keypad	
ACCESSORIES		





9447 DC Vehicle Charger Cord 9483 Power Supply

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 04-24-24