# 472-PWC-FIRES

## Mobil-Medizin

SCBA FIRES System Case

This Peli™ iM2950 case securely transports an SCBA system with space to store three replacement filters. This watertight & crushproof case features a hinged lid, five Press & Pull™ latches, two double-layered soft grip handle, two padlock-able hasps, a Vortex™ valve and comes with a lifetime guarantee.

• Custom interior designed to hold a harness with cylinder attached, regulator and pressure gauge
• Included strap secures the mask
• Room to store up to three extra filters

## GRÖSSE

| | |
|---|---|
| **INNERE** | 29.00 x 18.00" x 10.50 (73.7 x 45.7 x 26.7 cm) |
| **AUSSEN** | 31.30 x 20.40" x 12.20 (79.5 x 51.8 x 31 cm) |
| **Deckeltiefe** | 2.00" (5.1 cm) |
| **Bodentiefe** | 8.50" (21.6 cm) |
| **Gesamttiefe** | 10.5" (26.7 cm) |
| **Innenvolumen** | 3.17 ft³ (0.09 m³) |

## MATERIALEN

| | |
|---|---|
| **Gehäuse** | Injection Molded HPX™ high performance resin |
| **Verschluss** | Valox - Polybutylene Terephthalate (PBT) |
| **Verschluss (Alt)** | Xenoy - Polyester/Polycarbonate blend |
| **O-Ring Dichtung** | EPDM |
| **Stifte** | Stainless Steel |
| **Schaumstoff** | Aluminum |
| **Ausgleichsschraube** | 1.3/1.35 polyester |
| **Ausgleichsschraube (Alt)** | Valox - Polybutylene Terephthalate (PBT) |
| **Ausgleichsventil** | Xenoy - Polyester/Polycarbonate blend |

## FARBEN

Black

OD Green

## TEMPERATUR

| | |
|---|---|
| **min. Temperatur** | -20°F (-28.9 °C) |
| **max. Temperatur** | 140°F (60 °C) |

**Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

*Document created on 12-16-25*