



## 472-PWC-FIRES

### Mobil-Medizin

#### SCBA FIRES System Case

This Peli™ iM2950 case securely transports an SCBA system with space to store three replacement filters. This watertight & crushproof case features a hinged lid, five Press & Pull™ latches, two double-layered soft grip handle, two padlock-able hasps, a Vortex™ valve and comes with a lifetime guarantee.

- Custom interior designed to hold a harness with cylinder attached, regulator and pressure gauge
- Included strap secures the mask
- Room to store up to three extra filters



### GRÖSSE

|                     |                                                |
|---------------------|------------------------------------------------|
| <b>INNERE</b>       | 29.00 x 18.00" x 10.50 (73.7 x 45.7 x 26.7 cm) |
| <b>AUSSEN</b>       | 31.30 x 20.40" x 12.20 (79.5 x 51.8 x 31 cm)   |
| <b>Deckeltiefe</b>  | 2.00" (5.1 cm)                                 |
| <b>Bodentiefe</b>   | 8.50" (21.6 cm)                                |
| <b>Gesamttiefe</b>  | 10.5" (26.7 cm)                                |
| <b>Innenvolumen</b> | 3.17 ft <sup>3</sup> (0.09 m <sup>3</sup> )    |

### MATERIALEN

|                                 |                                              |
|---------------------------------|----------------------------------------------|
| <b>Gehäuse</b>                  | Injection Molded HPX™ high performance resin |
| <b>Verschluss</b>               | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Verschluss (Alt)</b>         | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring Dichtung</b>          | EPDM                                         |
| <b>Stifte</b>                   | Stainless Steel                              |
| <b>Schaumstoff</b>              | Aluminum                                     |
| <b>Ausgleichsschraube</b>       | 1.3/1.35 polyester                           |
| <b>Ausgleichsschraube (Alt)</b> | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Ausgleichsventil</b>         | Xenoy - Polyester/Polycarbonate blend        |

### FARBEN

|                                                                                           |                                                                                              |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
|  Black |  OD Green |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|

### TEMPERATUR

|                        |                  |
|------------------------|------------------|
| <b>min. Temperatur</b> | -20°F (-28.9 °C) |
| <b>max. Temperatur</b> | 140°F (60 °C)    |

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 10-25-25*