



3310ELS

Emergency Lighting Station

When the power goes out, the Peli™ 3310 ELS appears: a self-contained glowing beacon and flashlight that's easy to locate in the dark. Housed in a clear tamper-proof case, the Peli™ 3310 ELS mounts to the wall in the home, office or factory, making it available during any power outage. The new Peli™ 3310 ELS: You'll never lose it.

- Great for emergency preparedness
- Signaling mode for search and rescue scenarios
- Wall mountable case for ease of access (hardware included)
- Ingress Protected IPX8 Submersible
- 378 lumens of light output



DIMENSIONS

| | |
|--------|-----------------|
| Length | 6.14" (15.6 cm) |
|--------|-----------------|

MATERIALS

| | |
|--------|--------------------------------------|
| Body | Photo luminescent Polycarbonate (PC) |
| O-Ring | EPDM |
| Lens | Polycarbonate (PC) |

COLOURS

| |
|--|
|  Photoluminescent |
|--|

LIGHT SPECS

| | |
|-----------|-----|
| Lamp Type | LED |
|-----------|-----|

POWER

| | |
|--------------------|----------|
| Battery Size | AA |
| Battery Type | Alkaline |
| Battery Quantity | 3 |
| Batteries Included | yes |
| Volts | 4.5v |

WEIGHT

| | |
|--------------------------|-----------------|
| Weight With Batteries | 6.2 oz (176 gr) |
| Weight Without Batteries | 3.7 oz (105 gr) |

SWITCH

| | |
|-------------|-------------|
| Switch Type | Push Button |
|-------------|-------------|

Light Modes

High / Low / Flashing

OTHER

Minimum Pack

1

| FL1 STANDARD | HIGH | LOW |
|---|---------------|--------------|
|  | 378 LUMENS | 39 LUMENS |
|  | 8h 0mins | 202h 0mins |
|  | 196m | 62m |
|  | 9580cd | 961cd |
|  | IPX8 (1m) | |

ACCESSORIES



2469P
Replacement Battery

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 09-09-25