



# 1510

## Protector

Carry-On Case

The original case introduced over 45 years ago has since evolved into the global standard for equipment protection. The Protector Case series is designed to survive and trusted to travel to the harshest environments on earth.

The Peli 1510 Protector Case provides military-grade protection for a wide variety of gear, from camera equipment to camping kits. It is available with foam, without foam, padded dividers, or TrekPak dividers. The Peli 1510 Protector Case is the maximum airline carry-on size, so you can travel with your sensitive gear close at hand.

(Check with your airline for exact measurement requirements)

- Watertight, crushproof, and dustproof construction for total protection in any environment
- Cabin friendly design suitable for carry on travel on many airlines, subject to individual airline policies\*
- O-ring seal
- Customizable interior options including foam, padded dividers, or TrekPak dividers
- Precision foam customization available for a perfect fit around your equipment
- Case personalization with vinyls for names, logos, or custom graphics
- Bold color options including pink, yellow, black, orange and more
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Peli™ Limited Lifetime Guarantee\*\*



### CONFIGURATIONS



### DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (LxWxD)</b>      | 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) |
| <b>Exterior (LxWxD)</b>      | 22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm) |
| <b>Lid Depth</b>             | 1.79" (4.5 cm)                                |
| <b>Bottom Depth</b>          | 5.79" (14.7 cm)                               |
| <b>Total Depth</b>           | 7.58" (19.3 cm)                               |
| <b>Int Volume</b>            | 0.96 ft <sup>3</sup> (0.027 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                |

### MATERIALS

|                   |                     |
|-------------------|---------------------|
| <b>Body</b>       | Polypropylene       |
| <b>Latch</b>      | ABS                 |
| <b>O-Ring</b>     | Polymer             |
| <b>Pins</b>       | Stainless Steel     |
| <b>Foam</b>       | 1.3 lb Polyurethane |
| <b>Purge Body</b> | ABS                 |

**Purge Vent**

3 Micron Hydrophobic Non-Woven

**COLOURS**

- Black
- Desert Tan
- Orange
- Yellow
- Pink

**WEIGHT**

|  |                      |
|--|----------------------|
| <b>Weight With Foam</b>                  | 13.60 lbs (6.17 kg)  |
| <b>Weight Empty</b>                      | 11.99 lbs (5.44 kg)  |
| <b>Buoyancy</b>                          | 64.15 lbs (29.1 kg)  |
| <b>Weight With TrekPak / Foam Hybrid</b> | 14.94 lbs (6.78 kg)  |
| <b>Master Pack Weight</b>                | 32.43 lbs (14.71 kg) |

**TEMPERATURE**

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 190°F (87.8 °C) |

**CERTIFICATIONS**

**IP67**  
**Def Stan 81-41**

**OTHER**

|                          |     |
|--------------------------|-----|
| <b>Wheels</b>            | 2   |
| <b>Extendable Handle</b> | yes |
| <b>Master Pack</b>       | 2   |
| <b>Nameplate</b>         | yes |
| <b>Reduced Area</b>      | yes |
| <b>Military</b>          | yes |

**ACCESSORIES**



**1511**  
4 pc. Replacement Foam Set



**1513**  
Replacement O-ring



**1515**  
Padded Divider Set



**1519**  
Lid Organizer



**1510EUTP**  
TrekPak Case Divider Kit



**1510TPKIT**  
TrekPak Case Divider Kit



**1510TPDIV**  
Extra TrekPak Dividers



**1507QM**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**1510MP**  
EZ-Click™ MOLLE Panel



**RucPac-Pro-1**  
RucPac Pro Hardcase  
Backpack Conversion



**RucPac-normal**  
RucPac Standard Hardcase  
Backpack Conversion

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 04-27-26*