



# 1560SC2

## Protector

### Studio Case

Built for creators who move fast and work in demanding environments, the Peli Protector Studio Case transforms the legendary Protector into a complete mobile workflow system. Engineered with next-generation HPX<sup>®</sup> polymer for superior impact resistance and long-term durability, it delivers the trusted watertight, crushproof, and dustproof protection professionals rely on. Purpose-configured for photography and video equipment, the Studio Case combines a fully customizable padded divider interior with integrated lid organization and in-case lighting, keeping every accessory protected, visible, and ready to deploy. New smooth-rolling wheels and upgraded push-button latches make transport and access faster and more intuitive wherever the job takes you.

- **Waterproof, Crushproof & Dustproof** - The legendary Protector, now built with next-generation HPX<sup>®</sup> polymer for superior impact resistance.
- **Integrated Lid Organization** - GridPoint Panel with included ModPak Utility Pouches keeps accessories organized, visible, and easy to access.
- **Professional In-Case Lighting** - ModLight Pivot illuminates equipment inside the case for improved visibility in low-light environments.
- **Upgraded Push-Button Latches** - New push-button latches deliver secure, intuitive access with positive engagement—even while wearing gloves.
- **Smooth-Rolling Mobility** - New quiet-rolling wheels with stainless steel bearings provide smoother transport across terminals, locations, and job sites.
- **Customizable Padded Interior** - Configurable padded divider system securely organizes and protects camera, video, and production equipment.
- **Automatic Pressure Equalization Valve** - Balances interior pressure after altitude or temperature changes for easier opening.
- **Stainless Steel Hardware** - Corrosion-resistant hardware and reinforced padlock protectors built for long-term durability.
- **Made in the USA** - Designed and manufactured in the USA.
- **Lifetime Guarantee of Excellence** - Backed by Peli's legendary lifetime guarantee.



## DIMENSIONS

|                              |                                                |
|------------------------------|------------------------------------------------|
| <b>Interior (L×W×D)</b>      | 19.92 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm)    |
| <b>Exterior (L×W×D)</b>      | 22.07 x 17.92" x 10.42 (56.1 x 45.5 x 26.5 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                 |
| <b>Bottom Depth</b>          | 7.00" (17.8 cm)                                |
| <b>Total Depth</b>           | 9" (22.9 cm)                                   |
| <b>Int Volume</b>            | 1.55 ft <sup>3</sup> (0.044 m <sup>3</sup> )   |
| <b>Padlock Hole Diameter</b> | 5/16" (12.7 cm)                                |

## MATERIALS

|                   |                                |
|-------------------|--------------------------------|
| <b>Body</b>       | HPX <sup>®</sup>               |
| <b>O-Ring</b>     | Polymer                        |
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | 1.3 lb Polyurethane            |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLOURS

■ Black

WEIGHT

|                     |                       |
|---------------------|-----------------------|
| <b>Weight Empty</b> | 17.00 lbs (7.71 kg)   |
| <b>Weight</b>       | 18.70 lbs (8.48 kg)   |
| <b>Buoyancy</b>     | 115.00 lbs (52.16 kg) |

TEMPERATURE

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 10°F (-12.2 °C) |

OTHER

|               |   |
|---------------|---|
| <b>Wheels</b> | 2 |
|---------------|---|

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 10-07-26*