

1510LFC Protector Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

$\boldsymbol{\cdot}$ 2 in 1 protection: detachable computer sleeve and accessories pouch

- Maximum airline carry on size*
- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Fits notebook computers up to 14.4" x 11.1" x 1.7" (36.58 x 28.19 x 4.32 cm)
- Peli's legendary lifetime guarantee**
- * Check with your airline for exact measurement requirements.
- * Where applicable by law

DIMENSIONS

| Interior (L×W×D) | 19.75 x 11.00" x 7.60 (50.2 x 27.9 x 19.3 cm) |
|-----------------------|---|
| Exterior (L×W×D) | 22.00 x 13.81" x 9.00 (55.9 x 35.1 x 22.9 cm) |
| Lid Depth | 1.79" (4.5 cm) |
| Bottom Depth | 5.79" (14.7 cm) |
| Total Depth | 7.58" (19.3 cm) |
| Int Volume | 0.96 ft ³ (0.027 m ³) |
| Padlock Hole Diameter | 5/16" (12.7 cm) |

MATERIALS

| Body | Polypropylene |
|------------|--------------------------------|
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

Black

WEIGHT



| Weight Empty | 11.99 lbs (5.4 kg) |
|--------------------|---------------------|
| Buoyancy | 64.15 lbs (29.1 kg) |
| Master Pack Weight | 32.43 lbs (14.7 kg) |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) |
|---------------------|-----------------|
| Maximum Temperature | 190°F (87.8 °C) |

CERTIFICATIONS

IP67 Def Stan 81-41

OTHER

| Wheels | 2 |
|-------------------|-----|
| Extendable Handle | yes |
| Master Pack | 2 |
| Nameplate | yes |
| Reduced Area | yes |
| Military | yes |

ACCESSORIES



1513 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel



RucPac-Pro-1 RucPac Pro Hardcase Backpack Conversion



RucPac-normal RucPac Standard Hardcase Backpack Conversion

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-31-25