

1650EU

Protector

The Peli 1650 is a large sized protector case that comes with three comfortable, fold down, rubber over-moulded carrying handles as well as a retractable handle and 4 strong polyurethane wheels with stainless steel bearings. Like all other Peli Protector cases, this rugged case is also designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid and stainless steel hardware. Rugged, uncompromising and trusted, Peli cases protect what matters to you, from the everyday to the extraordinary. Peli Protector Cases are made with copolymer polypropylene and cutting edge technology, which makes them virtually indestructible and resistant to the most extreme conditions. Proven for over 45 years in the most demanding environments. Engineered and manufactured in the U.S and in Germany. Guaranteed for Life and sustainable due to its long life.

- · 4 strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- 2 level Pick N Pluck™ with convoluted lid foam
 Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- · Made in Germany



CONFIGURATIONS



1650EU Standard



1654 With Padded Dividers



1650NF No Foam



1650WF With Foam

DIMENSIONS

Interior (L×W×D) 28.41 x 17.40" x 10.64 (72.2 x 44.2 x 27 cm) Exterior (L×W×D) 31.55 x 20.51" x 12.47 (80.1 x 52.1 x 31.7 cm)

Lid Depth 1.81" (4.6 cm) **Bottom Depth** 8.84" (22.5 cm) **Total Depth** 10.65" (27.1 cm) **Int Volume** 3.04 ft³ (0.086 m³) Padlock Hole Diameter 5/16" (12.7 cm)

MATERIALS

Body

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Black Desert Tan

WEIGHT

 Weight With Foam
 28.06 lbs (12.7 kg)

 Weight Empty
 24.03 lbs (10.9 kg)

 Buoyancy
 181.00 lbs (82.1 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41 ATA 300

OTHER

Wheels 4
Extendable Handle yes
Master Pack 1
Nameplate yes
Reduced Area yes
Military yes

ACCESSORIES



1651 4 pc. Replacement Foam Set



1653 Replacement O-ring



1655 Padded Divider Set



1659 Photo/Lid Organizer



1650EUTP TrekPak Case Divider Kit







1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 10-29-25