



1505

Air

The 1505 Air case is a versatile, shallow attaché-style case with built-in functionality to support panel mounting in the lid and base. Protect laptops and sensitive electronics or leverage the out-of-the-box panel mounting capability to engineer your own mobile communications system, cradlepoint, or battery charging station. Whether you're a construction professional transporting your laptop to the site, a law enforcement team relying on a cradlepoint to maintain communications, or prototyping a new medical device, the 1505 Air case delivers the ultimate combination of durability, portability, and versatility.

- Integriertes Blendensystem für die Panelmontage
- Wasserdicht, bruchstark, staubdicht
- IP67- und MIL-SPEC-zertifiziert
- Superleichtes proprietäres HPX²™ Polymer - bis zu 40 % leichter
- Press and Pull™ Verschlüsse
- Automatisches Druckausgleichsventil - gleicht den Innendruck aus, hält Wasser fern
- Klappbarer, spritzbeschichteter Griff
- Wasserdichte O-Ring-Dichtung
- Vorhängeschloss-Verstärkung aus Edelstahl
- Limited Lifetime Warranty



KONFIGURATIONEN



1505
Standard



1505NF
No Foam



1505WF
With Foam



1505TP
With TrekPak Divider System

GRÖSSE

INNERE	18.29 x 13.26" x 5.46 (46.5 x 33.7 x 13.9 cm)
AUSSEN	20.22 x 16.38" x 6.10 (51.4 x 41.6 x 15.5 cm)
Deckeltiefe	1.93" (4.9 cm)
Bodentiefe	3.53" (9 cm)
Gesamttiefe	5.46" (13.9 cm)
Innenvolumen	0.77 ft ³ (0.022 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALIEN

Gehäuse	Proprietary Polypropylene Blend
Verschluss	ABS
O-Ring Dichtung	EPDM
Stifte	Stainless Steel

Schaumstoff	Polyurethane
Ausgleichsschraube	ABS
Ausgleichsventil	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven
Handgriff	Polypropylene and Thermoplastic Rubber Side Handle

FARBEN

■ Black

GEWICHT

Gewicht mit Schaumstoff	6.55 lbs (3 kg)
Gewicht ohne Schaumstoff	5.80 lbs (2.6 kg)
Schwimmfähigkeit	54.00 lbs (24.5 kg)

TEMPERATUR

min. Temperatur	0°F (-17.8 °C)
max. Temperatur	140°F (60 °C)

ZUBEHÖR



1505FS
3 St. Ersatz-Schaumstoffeinsätze



1472
Shoulder Strap

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 12-09-25