



## 2460Z1 StealthLite™

The rechargeable version of the StealthLite™ 2410 LED. The StealthLite™ Rechargeable 2460Z1 LED uses the 2469P NiMH battery and comes with the charger base unit cat # 2480F that can be installed at home or work using the 220V transformer cat # 2468Z1. Certified to ATEX Zone 1 (Category 2). Note, this charger base does not work on 12v systems.



### DIMENSIONS

---

**Length** 7.00" (17.8 cm)


### MATERIALS

---

**Body** Anti-static Impact Modified PC/PBT  
**O-Ring** Ethylene Propylene  
**Lens** Polycarbonate (PC)  
**Shroud** Anti-static Impact Modified PC/PBT  
**Contact Spring Retainer** Stainless Steel / Phosphore Bronze

### COLOURS

---

 High Visibility Yellow

### LIGHT SPECS

---

**Lamp Type** LED

### POWER

---

**Battery Size** AA  
**Battery Type** NiMH  
**Battery Quantity** 4  
**Batteries Included** yes  
**Rechargeable** yes  
**Charge Time** 8 hrs  
**Volts** 4.8v

### WEIGHT

---

**Weight With Batteries** 7.8 oz (221 gr)  
**Weight Without Batteries** 4.4 oz (125 gr)  
**Packaged Weight** 1.4 oz (40 gr)

### SWITCH

---

**Switch Type** One-handed Safety Switch  
**Light Modes** On / Off

## CERTIFICATIONS

---

**ATEX Zone 1**

## OTHER

---

**Minimum Pack** 1  
**Military** yes  
**Package Code** C

### FL1 STANDARD HIGH



## ACCESSORIES

---



**0770**  
Helmet Light Holder



**2480F**  
Deck/Dash Charger Base Unit



**2469P**  
Replacement Battery

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 06-15-26