



iM2975

Storm

Travel Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- Five Press & Pull Latches
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Powerful Hinges
- O-ring seal



CONFIGURATIONS



iM2975
Standard



iM2975-X0000
No Foam



iM2975-X0002
With Padded Dividers



iM2975-X0001
With Foam



WINE-20B
20-Bottle Wine



WINE-24B
24-Bottle Wine

DIMENSIONS

Interior (L×W×D)	29.00 x 18.00" x 13.80 (73.7 x 45.7 x 35.1 cm)
Exterior (L×W×D)	31.30 x 20.40" x 15.50 (79.5 x 51.8 x 39.4 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	11.80" (30 cm)
Total Depth	13.8" (35.1 cm)
Int Volume	4.17 ft ³ (0.118 m ³)
Padlock Hole Diameter	0.28" (0.7 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS



Black



OD Green

WEIGHT

Weight With Foam	29.50 lbs (13.38 kg)
Weight Empty	22.80 lbs (10.34 kg)
Buoyancy	250.02 lbs (113.41 kg)
Master Pack Weight	31.50 lbs (14.29 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

IP67

OTHER

Extendable Handle	yes
Master Pack	1
Military	yes

ACCESSORIES



iM29XX-UTILITYORG
Utility Organizer



iM2975-FOAM
8 pc. Replacement Foam Set



iM-LIDSTAY
Lid Stay




1506TSA
TSA Lock



1500D
Desiccant Silica Gel



iM2975-M4-BEZEL
Base Bezel Kit (Metric)



iM2975-M4-BEZEL-L
Lid Bezel Kit (Metric)

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 06-08-26