



1050 Micro

From small sensitive components to smartphones, protect your gear from the elements in a crushproof, watertight, & dustproof Micro Case from Peli.

- ***Case is able to be submerged under 1 meter of water for up to 30 minutes in accordance with IP67 testing parameters**
- **Available in clear with color liner or solid**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Carabiner
- Easy open latch
- Rubber liner for extra protection doubles as o-ring seal
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

| | |
|-------------------------|--|
| Interior (LxWxD) | 6.31 x 3.68" x 2.75 (16 x 9.3 x 7 cm) |
| Exterior (LxWxD) | 7.99 x 5.06" x 3.12 (20.3 x 12.9 x 7.9 cm) |
| Lid Depth | 0.69" (1.8 cm) |
| Bottom Depth | 1.94" (4.9 cm) |
| Total Depth | 2.63" (6.7 cm) |
| Int Volume | 0.04 ft ³ (0.001 m ³) |

MATERIALS

| | |
|-------------------|--------------------------------------|
| Body | Polycarbonate (PC) |
| Latch | Xylex |
| O-Ring | Thermoplastic Rubber |
| Pins | Stainless Steel |
| Foam | TL - 426 4 lb. Esther |
| Purge Body | Polycarbonate (PC) |
| Purge Vent | Polyester Spun-Bond ePTFE Oleophobic |

COLOURS

| | | | |
|---|--|---|---|
|  Black |  Yellow |  Black - Clear |  Yellow - Clear |
|---|--|---|---|

WEIGHT

| | |
|---------------------------|-------------------|
| Weight With Foam | 0.83 lbs (0.4 kg) |
| Weight Empty | 0.81 lbs (0.4 kg) |
| Buoyancy | 1.74 lbs (0.8 kg) |
| Master Pack Weight | 5.88 lbs (2.7 kg) |

TEMPERATURE

| | |
|----------------------------|------------------|
| Minimum Temperature | -10°F (-23.3 °C) |
| Maximum Temperature | 199°F (92.8 °C) |

CERTIFICATIONS

IP67

OTHER

| | |
|---------------------|-----|
| Minimum Pack | 6 |
| Master Pack | 6 |
| Military | yes |

ACCESSORIES



1052
Pick N Pluck™ Foam Insert

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-24-25