



# SUPER-V-SERIES-3U

## Super V 3U

- Fixed square hole frame for universal equipment fit
- 2" Front Lid, 5" Rear Lid
- Anti-reflective black hardware
- Coupling catches for secure stacking
- Molded in rear edge casters with handles on the lid for ease of movement
- Comfort Grip plastic handles
- High-strength steel rack frame supports equipment from 10 - 50 kg
- Designed to meet the requirements of Def Stan 81-41 Level J, Mil Standard 810, STANAG 4340 and other European standards.
- Designed to meet ANSI/EIA-310-C for universal rack mounting hole pattern
- 10 different models, frame heights 4-12U in two depths, 480 and 610mm
- Metric M6 clip nuts for more flexibility in mounting equipment
- Lid hangers for lid storage while in use
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- REACH and RoHs compliant



### DIMENSIONS

<b>Exterior (LxWxD)</b>	38.50 x 28.30" x 11.40 (97.8 x 71.9 x 29 cm)
<b>Rack Height</b>	5.25" (13.3 cm)
<b>Rack Depth</b>	24.00" (61 cm)
<b>Interior Lid Depth</b>	2.20" (5.6 cm)
<b>Interior Back Lid Depth</b>	5.20" (13.2 cm)

### MATERIALS

<b>Body</b>	RotoMolded Polyethylene
<b>O-Ring</b>	Silicone Sponge
<b>Purge Body</b>	Aluminum
<b>Hardware</b>	Stainless Steel (Black Oxide) / RoHs Nickel Black
<b>Frame</b>	Steel (Clear Coated)

### COLOURS

- Black

### WEIGHT

<b>Weight</b>	50.00 lbs (22.68 kg)
---------------	----------------------

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 06-15-26