SUPER-V-SERIES-4U

Super V

4U

• SUPER V-SERIES 4U, 2111-02/29/05W
• Fixed square hole frame for universal equipment fit
• 2” Front Lid, 5” Rear Lid
• Anti-reflective black hardware
• Coupling catches for secure stacking
• Available in 3U, 4U, 5U, 7U, 9U, 11U, and 14U
• Weight ranges for 7U – 14U = 100-170lbs per case
• Molded in rear edge casters with handles on the lid for ease of movement
• Comfort Grip plastic handles
• Metric M6 clip nuts for more flexibility in mounting equipment
• Engineered to provide secure transport for rack mountable electronics
• Equipment payload weight ranges for 3U – 5U = 80-100 lbs. (36-45 kg) per case
• Lid hangers for lid storage while in use
• Sealed gasket and PRV keeps container watertight and eliminates over pressurization
• REACH and RoHs compliant



DIMENSIONS

Exterior (L×W×D)	38.50 x 28.30" x 13.10 (97.8 x 71.9 x 33.3 cm)
Rack Height	7.00" (17.8 cm)
Rack Depth	24.00" (61 cm)
Interior Lid Depth	2.20" (5.6 cm)
Interior Back Lid Depth	5.20" (13.2 cm)

MATERIALS

Body	RotoMolded Polyethylene
O-Ring	Silicone Sponge
Purge Body	Aluminum
Hardware	Stainless Steel (Black Oxide) / RoHs Nickel Black
Frame	Steel (Clear Coated)

COLOURS

Black

WEIGHT

Weight 53.00 lbs (24.04 kg)

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 11-12-26