



# 1610M

## Protector

### Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings**
- **Water resistant, crushproof, and dust resistant**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



## CONFIGURATIONS



**1610M**  
Standard



**1610MNF**  
No Foam



**1610MWF**  
With Foam

## DIMENSIONS

<b>Interior (LxWxD)</b>	21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm)
<b>Exterior (LxWxD)</b>	26.20 x 23.00" x 13.68 (66.5 x 58.4 x 34.7 cm)
<b>Lid Depth</b>	2.05" (5.2 cm)
<b>Bottom Depth</b>	8.57" (21.8 cm)
<b>Total Depth</b>	10.62" (27 cm)
<b>Int Volume</b>	2.23 ft <sup>3</sup> (0.063 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Black
---

WEIGHT

Weight With Foam	29.10 lbs (13.2 kg)
Weight Empty	26.30 lbs (11.9 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP57
------

OTHER

Wheels	2
Extendable Handle	yes
Master Pack	1
Nameplate	yes
Military	yes

ACCESSORIES

				
<b>1609</b> Lid Organizer	<b>1611</b> 5 pc. Replacement Foam Set	<b>1615</b> Padded Divider Set	<b>1623</b> Replacement O-ring	<b>1507</b> Quick Mounts - set of 4
				
<b>1506TSA</b> TSA Lock	<b>1500D</b> Desiccant Silica Gel			

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 09-09-25*