



9470M

"M" for mobility, the 9470M is built with a set of XL wheels providing easy transport over rough terrain. The all new and extremely powerful 9470M Remote Area Lighting System (RALS) provides convenient and ecologically responsible alternatives to wasteful generator powered lights. Engineered with the Intelligent Control System which calculates and displays current battery life. Additionally, it allows the user to regulate the intensity of the light, choose the desired run time or select from three pre-set power levels. Built with versatility in mind, the 9470M RALS features four telescopic masts (each extends to nearly 6 feet) and four 360° articulating light heads. The system's next-generation LEDs combine to radiate up to 24,000 lumens (6,000 per light head). For extended applications, the 9470M can run continuously on wall power. The ability to leave on charge allows you to always be prepared. A 12 volt power port including a dual USB adapter provides power for many peripheral devices. Built self-contained in a tough-as-nails Peli case, the 9470M is compact and includes the multi-terrain trolley with a retractable pull handle and stainless steel ball-bearing 1.5 inch polyurethane wheels.

CAUTION: The Peli Products RALS models 9460 and 9470 contain sealed lead acid batteries that can generate hydrogen gas when charging. It is imperative that these products are charged, as instructed, with the case lid open to allow any gases to escape as charging with the lid closed poses a significant hazard. Failure to abide by this instruction could result in injury and/or damage to property. Please refer to the warnings provided in the instructions for the unit and on a decal affixed to the inside of the case adjacent to the cavity where the charger unit is packed.

NEW UPGRADED SPECS

- Ausziehbare duale LED-Lampenköpfe
- In einem Peli Schutzkoffer integriert
- Geräuschloser Betrieb
- Kühle Betriebstemperaturen
- Keine Abluft
- Stetige Batteriestandanzeige mit Blinkwarnung bei niedrigem Batteriestan
- Dualer USB Netzadapter
- Multi-terrain trolley w/ 1.5" wheels
- RoHS and CE Compliant



GRÖSSE

Head (LxWxD)	8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)
Closed (LxWxD)	24.75 x 20.00" x 11.75 (62.9 x 50.8 x 29.8 cm)
Mastlänge	82.00" (208.3 cm)
Kabellänge	13.78" (35 cm)

MATERIALEN

Gehäuse	Polypropylene
Kopf	Aluminum
Mast	Aluminum
Linse	Polycarbonate (PC)

FARBEN

 Black	 Yellow
---	--

LIGHT SPECS

Lumen Hoch	24000
-------------------	-------

Lampenköpfe	4
Lampentyp	LED
Anzahl der LEDs	40
Leuchtwinkel	120°
IP-Schutzklasse	54

POWER

Brenndauer Hoch	2.75 hrs
Brenndauer Niedrig	24.00 hrs
Batterietyp	Sealed Lead Acid (SLA)
Rechargeable	ja
Batteriebrenndauer	500 cycles
Ladezeit	8 hrs
Batterieladezustandsanzeige	iControl
Buchsen primär	4
Volt	12.0v

GEWICHT

Gewicht	108.00 lbs (49 kg)
----------------	--------------------

SWITCH

Schaltertyp	iControl Keypad
--------------------	-----------------

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 06-13-25