



## iM3075

### Storm

#### Transport Case

The Pelj™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- Seven Press & Pull Latches
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- In-line Wheels
- Powerful Hinges
- O-ring seal



## CONFIGURATIONS



**iM3075**  
Standard



**iM3075-X0000**  
No Foam



**iM3075-X0002**  
With Padded Dividers



**iM3075-X0001**  
With Foam

## DIMENSIONS

|                              |  |
|------------------------------|--|
| <b>Interior (LxWxD)</b>      | 29.80 x 20.80" x 17.80 (75.7 x 52.8 x 45.2 cm) |
| <b>Exterior (LxWxD)</b>      | 33.30 x 24.40" x 19.30 (84.6 x 62 x 49 cm)     |
| <b>Lid Depth</b>             | 4.00" (10.2 cm)                                |
| <b>Bottom Depth</b>          | 13.75" (34.9 cm)                               |
| <b>Total Depth</b>           | 17.75" (45.1 cm)                               |
| <b>Int Volume</b>            | 6.38 ft <sup>3</sup> (0.181 m <sup>3</sup> )   |
| <b>Padlock Hole Diameter</b> | 0.35" (0.9 cm)                                 |

## MATERIALS

|                         |  |
|-------------------------|--|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenoy - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM   |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Pins (Alt)</b>       | Aluminum                                     |
| <b>Foam</b>             | 1.3/1.35 polyester                           |
| <b>Purge Body</b>       | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Body (Alt)</b> | Xenoy - Polyester/Polycarbonate blend        |
| <b>Purge Vent</b>       | Gortex membrane                              |

## COLOURS

■ Black

■ OD Green

## WEIGHT

|                           |                        |
|---------------------------|------------------------|
| <b>Weight With Foam</b>   | 45.00 lbs (20.41 kg)   |
| <b>Weight Empty</b>       | 31.50 lbs (14.29 kg)   |
| <b>Buoyancy</b>           | 388.20 lbs (176.08 kg) |
| <b>Master Pack Weight</b> | 37.00 lbs (16.78 kg)   |

## TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |

## CERTIFICATIONS

**IP67**

## OTHER

|                          |     |
|--------------------------|-----|
| <b>Extendable Handle</b> | yes |
| <b>Master Pack</b>       | 1   |
| <b>Military</b>          | yes |

## ACCESSORIES



**iM3075-FOAM**  
7 pc. Replacement Foam Set




**iM3075-DIV**  
Padded Divider Set



**iM-LIDSTAY**  
Lid Stay



**iM3075-UTILITYORG**  
Utility Organizer



**iM3075-M4-BEZEL-L**  
Lid Bezel Kit (Metric)



**iM3075-MBEZ-B**  
Base Bezel Kit (Metric)



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 07-07-26