



9050

The new 9050 lantern is the next generation of Peli High Performance lighting.

The 9050 includes industry first technology - The flexible battery system allows you to select between Li-ion, AA alkaline or AA NiMH to operate the light. Four battery slots let you maximize runtime. The quick-change battery system means that you have continuous lighting to get the job done. Select between spot, flood, spot/flood, or flashing modes to find the right beam for your job. The spot/flood light head outputs up to 3369 lumens without the need for diffusers or attachments so you can quickly choose the right beam type for your job. A redesigned charger base makes mounting and dismounting the lantern quick and easy. Rear taillights with adjustable colors make notification or identification as simple as pressing the dedicated switch.

The Peli 9050 delivers the innovation, durability and best-in-class performance that you have come to expect from Peli.

- Flexible battery system that can run on Li-ion battery packs, AA Alkaline or AA NiMH cells
- 4 battery slots to extend runtime or reduce weight
- Spot, Flood, Spot/Flood and Flashing modes
- 3369 lumens of maximum light output
- Convenient charger base provides quick mounting and dismounting
- Rear taillights with dedicated switch and adjustable colors (Green, Blue, Red)
- IP67 Rating
- Glove-friendly switch activation
- Wide base for stability
- Battery status indicator switch
- Approved to NFPA (National Fire Protection Association) 1901



DIMENSIONS

| | |
|---------------|-----------------|
| Length | 8.03" (20.4 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|--------------------|
| Body | ABS |
| O-Ring | Buna-N |
| Lens | Polycarbonate (PC) |
| Shroud | ABS |

COLOURS

 Yellow

LIGHT SPECS

| | |
|----------------------------|-----------|
| Lamp Type | LED |
| Lamp Secondary Type | LED |
| Lamp Life | 50000 hrs |

POWER

| | |
|---------------------------|-------------|
| Battery Size | 18650 |
| Battery Type | Lithium-Ion |
| Battery Quantity | 2 |
| Batteries Included | yes |
| Rechargeable | yes |






Charge Time 5 hrs 30 mins
Battery Level Indicator RGB LED
Volts 7.2v

WEIGHT

Weight With Batteries 45.9 oz (1301 gr)
Weight Without Batteries 38.8 oz (1100 gr)

SWITCH


Switch Type Push Button
Light Modes High / Low / Flashing

| | FL1 STANDARD | SPOT / FLOOD | FLOOD | SPOT |
|---|--------------|--------------|-------------|-------------|
|  | 3369 LUMENS | | 1119 LUMENS | 2623 LUMENS |
|  | 2h 45mins | | 5h 30mins | 4h 15mins |
|  | 417m | | 47m | 489m |
|  | 43568cd | | 559cd | 59760cd |
|  | IP67 | | | |

ACCESSORIES



ADP05
DC12DV Direct Wire Adapter



ADP04
AC Adapter



ADP03
12V Vehicle Plug-In



BAT05
Replacement Lithium Ion Battery Pack



CHG04
High Power Charging Base

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-04-26