# 1560SC

## Protector

Studio Case



Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.
Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Padded removable sleeve for 15"-17" laptop computers**
- **Strong polyurethane wheels with stainless steel bearings**
- **Three removable accessory pouches**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Peli's legendary lifetime guarantee**
- This case may qualify as carry-on luggage on some airlines, check with your airline for more details
- * Where applicable by law

## DIMENSIONS

| | |
|---|---|
| **Interior (L×W×D)** | 19.92 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm) |
| **Exterior (L×W×D)** | 22.07 x 17.92" x 10.42 (56.1 x 45.5 x 26.5 cm) |
| **Lid Depth** | 2.00" (5.1 cm) |
| **Bottom Depth** | 7.00" (17.8 cm) |
| **Total Depth** | 9" (22.9 cm) |
| **Int Volume** | 1.55 ft³ (0.044 m³) |
| **Padlock Hole Diameter** | 5/16" (12.7 cm) |

## MATERIALS

| | |
|---|---|
| **Body** | Polypropylene |
| **Latch** | ABS |
| **O-Ring** | Polymer |
| **Pins** | Stainless Steel |
| **Foam** | 1.3 lb Polyurethane |
| **Purge Body** | ABS |
| **Purge Vent** | 3 Micron Hydrophobic Non-Woven |

## COLOURS

Black

## WEIGHT

| | |
|---|---|
| **Weight With Foam** | 18.18 lbs (8.25 kg) |
| **Weight Empty** | 17.00 lbs (7.71 kg) |

| | |
|---|---|
| **Buoyancy** | 115.00 lbs (52.16 kg) |
| **Master Pack Weight** | 21.00 lbs (9.53 kg) |

## TEMPERATURE

| | |
|---|---|
| **Minimum Temperature** | -40°F (-40 °C) |
| **Maximum Temperature** | 190°F (87.8 °C) |

## CERTIFICATIONS

**IP67**
**Def Stan 81-41**

## OTHER

| | |
|---|---|
| **Wheels** | 2 |
| **Extendable Handle** | yes |
| **Master Pack** | 1 |
| **Nameplate** | yes |
| **Military** | yes |

## ACCESSORIES



**0343**
Replacement O-ring



**1506TSA**
TSA Lock



**1500D**
Desiccant Silica Gel

**Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

*Document created on 10-29-26*