# 1930Z0

## L1™

Same features as L1™ 1930 LED with static-dissipation materials body. Being certified to ATEX safe for use in high-risk hazardous locations, Zone 0 (Category 1) areas, L1™ 1930Z0 LED is ideal for professionals who work in chemical, pharmaceutical, power, oil and gas, and fire rescue industries.




## DIMENSIONS

| | |
|---|---|
| **Length** | 2.64" (6.7 cm) |

## MATERIALS

| | |
|---|---|
| **Body** | Anti-static Impact Modified PC/PBT |
| **O-Ring** | Ethylene Propylene |
| **Lens** | Polycarbonate (PC) |
| **Shroud** | Anti-static Impact Modified PC/PBT |
| **Contact Spring Retainer** | Phosphore Bronze |

## COLOURS

Gray

## LIGHT SPECS

| | |
|---|---|
| **Lamp Type** | LED |

## POWER

| | |
|---|---|
| **Battery Size** | LR 44 |
| **Battery Type** | Alkaline |
| **Battery Quantity** | 4 |
| **Batteries Included** | yes |
| **Volts** | 6.0v |

## WEIGHT

| | |
|---|---|
| **Weight With Batteries** | 0.9 oz (26 gr) |
| **Weight Without Batteries** | 0.6 oz (17 gr) |

## SWITCH

| | |
|---|---|
| **Switch Type** | Push Button Tail |
| **Light Modes** | On / Off |

## CERTIFICATIONS

**ATEX Zone 0**

## OTHER

| | |
|---|---|
| **Minimum Pack** | 12 |
| **Military** | yes |
| **Package Code** | C |

| FL1 STANDARD | HIGH |
|---|---|
|  | 12 LUMENS |
|  | 4h 15mins |
|  | 17m |
|  | 70cd |
|  | IPX4 |

**Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

*Document created on 10-31-26*