# iM3200

## Storm

Long Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.
Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.



- Six Press & Pull Latches
- Two Padlockable Hasps
- Two Double-layered, Soft-grip Handles
- Vortex™ Valve
- Powerful Hinges
- O-ring seal
- Lightweight Strong HPX® Resin

## CONFIGURATIONS



**iM3200**
Standard



**iM3200-X0000**
No Foam



**iM3200-X0001**
With Foam

## DIMENSIONS

| | |
|---|---|
| **Interior (L×W×D)** | 44.00 x 14.00" x 6.00 (111.8 x 35.6 x 15.2 cm) |
| **Exterior (L×W×D)** | 47.20 x 16.50" x 6.70 (119.9 x 41.9 x 17 cm) |
| **Lid Depth** | 2.00" (5.1 cm) |
| **Bottom Depth** | 4.00" (10.2 cm) |
| **Total Depth** | 6" (15.2 cm) |
| **Int Volume** | 2.14 ft³ (0.061 m³) |
| **Padlock Hole Diameter** | 0.38" (1 cm) |

## MATERIALS

| | |
|---|---|
| **Body** | Injection Molded HPX™ high performance resin |
| **Latch** | Valox - Polybutylene Terephthalate (PBT) |
| **Latch (Alt)** | Xenoy - Polyester/Polycarbonate blend |
| **O-Ring** | EPDM |
| **Pins** | Stainless Steel |
| **Pins (Alt)** | Aluminum |
| **Foam** | 1.3/1.35 polyester |
| **Purge Body** | Valox - Polybutylene Terephthalate (PBT) |
| **Purge Body (Alt)** | Xenoy - Polyester/Polycarbonate blend |
| **Purge Vent** | Gortex membrane |

## COLOURS

Black

OD Green

## WEIGHT

| | |
|---|---|
| **Weight With Foam** | 21.10 lbs (9.57 kg) |
| **Weight Empty** | 17.70 lbs (8.03 kg) |
| **Buoyancy** | 136.09 lbs (61.73 kg) |

## TEMPERATURE

| | |
|---|---|
| **Minimum Temperature** | -20°F (-28.9 °C) |
| **Maximum Temperature** | 140°F (60 °C) |


## CERTIFICATIONS

**IP67**

## OTHER

| | |
|---|---|
| **Master Pack** | 1 |
| **Military** | yes |

## ACCESSORIES



**iM3200-FOAM**
4 pc. Replacement Foam Set



**iM-STRAP-S-VER2**
Padded Shoulder Strap



**iM-LIDSTAY**
Lid Stay



**1506TSA**
TSA Lock



**1500D**
Desiccant Silica Gel

**Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

*Document created on 10-31-26*