1615TRVL

Air

Travel Case

Stop rummaging through old luggage at check-in lines or remote base camps and travel smarter with Peli™ Air Travel Cases. Lid organizers have zippered compartments for stowing larger items and see-through mesh pockets secure passports and cables. Packing cubes keep gear tightly bundled and allow you to arrange your gear by stacking or grouping side by side. Peli™ Air Travel Cases are also built for versatility. Just remove the packing cubes and replace with optional Trekpak™ dividers, padded dividers or Pick N Pluck™ foam interior solutions (available separately).



- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- Maximum airline check-in size*
- *Check with your airline for exact measurement requirements
- Press and Pull™ Latches
- Lid Mesh and Zippered Storage Compartments
- Packing Cube Organizers
- Press and Pull Latches with TSA Key Locks
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified

DIMENSIONS

Interior (L×W×D)	29.59 x 15.50" x 9.38 (75.2 x 39.4 x 23.8 cm)
Exterior (L×W×D)	32.58 x 18.40" x 11.02 (82.8 x 46.7 x 28 cm)
Large Packing Cube (L×W×D)	17.52 x 15.51" x 11.61 (44.5 x 39.4 x 29.5 cm)
Small Packing Cube (L×W×D)	10.83 x 15.51" x 10.63 (27.5 x 39.4 x 27 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	7.38" (18.7 cm)
Total Depth	9.38" (23.8 cm)
Int Volume	2.49 ft³ (0.071 m³)
Large Packing Cube Volume	1.83 ft³ (0.052 m³)
Small Packing Cube Volume	1.03 ft³ (0.029 m³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black	Charcoal	Indigo	Oxblood

WEIGHT

Weight With Organizers	19.00 lbs (8.62 kg)

TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

OTHER

Wheels	2

ACCESSORIES



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



AIRHANDL
EZ-Pull Multi-Stage Air Handle

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 10-31-26