



## 0550

### Protector

#### Transport Case

With over 11 cubic feet (0.311 cubic meters) of space, you can store, protect, and move large loads in seconds. The reinforced honeycomb deck and lid construction provide support for heavy equipment, or multiple stacking on a 463L pallet. Opening the case at any altitude is not a problem- the dual integrated automatic pressure equalization valves keep moisture out and prevent vacuum lock, and the double wide grip makes lifting easy. With an IP55 certification, the 0550 Transport Case will protect your gear against rain and dirt. The 0550 Transport Case: Built to move-by forklift, by wheel, by hand.

- **Built to move: by forklift, by wheel or by hand**
- **Fit six 0550 Cases per 463L military pallet, 18 when stacked!**
- **Over 11ft<sup>3</sup> (.311m<sup>3</sup>) of storage space**
- Dual Integrated Automatic Pressure Equalization Valves
- Easy open double-throw latches
- Four extra-deep base-to-lid locking cleats ensure maximum stacking stability
- Locking metal Lidstays keep lid locked in open position
- O-ring seal for dust and water resistant seal (IP55)
- Open cell core with solid wall design - strong, light weight
- Optional Caster Wheel Kit complete with brakes
- Optional Pallet Riser Kit
- Reinforced honeycomb deck and lid for added strength
- Stainless steel hardware and padlock protectors
- Store documents outside the case with our Document Container
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



## CONFIGURATIONS



**0550**  
Standard



**0550NF**  
No Foam



**0550WF**  
With Foam

## DIMENSIONS

<b>Interior (LxWxD)</b>	47.57 x 24.07" x 17.68 (120.8 x 61.1 x 44.9 cm)
<b>Exterior (LxWxD)</b>	51.05 x 27.54" x 22.79 (129.7 x 70 x 57.9 cm)
<b>Lid Depth</b>	3.19" (8.1 cm)
<b>Bottom Depth</b>	14.49" (36.8 cm)
<b>Total Depth</b>	17.68" (44.9 cm)
<b>Int Volume</b>	11.72 ft <sup>3</sup> (0.332 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Black
---

WEIGHT

Weight With Foam	95.00 lbs (43.1 kg)
Weight Empty	79.20 lbs (35.9 kg)
Buoyancy	820.00 lbs (371.9 kg)
Master Pack Weight	95.00 lbs (43.1 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

Zone 20
---------

OTHER

Master Pack	1
-------------	---

ACCESSORIES

				
<b>0507</b> Caster Wheel Kit	<b>0508</b> Pallet Riser Kit	<b>0551</b> 6 pc. Replacement Foam Set	<b>1630DC</b> Document Container Accessory	<b>1507</b> Quick Mounts - set of 4
				
<b>1506TSA</b> TSA Lock	<b>1500D</b> Desiccant Silica Gel			

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 07-29-25*