


1610EU

Protector

The Peli 1610 is a large sized protector case that comes with 2 comfortable, fold down carrying handles as well as a retractable handle and 2 strong polyurethane wheels with stainless steel bearings. Like all other Peli Protector cases, this rugged case is also designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid and stainless steel hardware. Rugged, uncompromising and trusted, Peli cases protect what matters to you, from the everyday to the extraordinary. Peli Protector Cases are made with copolymer polypropylene and cutting edge technology, which makes them virtually indestructible and resistant to the most extreme conditions. Proven for over 45 years in the most demanding environments. Engineered and manufactured in the U.S and in Germany. Guaranteed for Life and sustainable due to its long life.



- · Watertight, crushproof, and dustproof
- 3 level Pick N Pluck[™] with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Made in Germany



CONFIGURATIONS



1610EU Standard



1614With Padded Dividers



1610NF No Foam



1610WF With Foam

DIMENSIONS

Interior (L×W×D) 21.68 x 16.62" x 10.56 (55.1 x 42.2 x 26.8 cm) Exterior (L×W×D) 24.71 x 19.58" x 11.93 (62.8 x 49.7 x 30.3 cm)

 Lid Depth
 2.06" (5.2 cm)

 Bottom Depth
 8.50" (21.6 cm)

 Total Depth
 10.56" (26.8 cm)

 Int Volume
 2.2 ft³ (0.062 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body

Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

 Weight With Foam
 22.49 lbs (10.2 kg)

 Weight Empty
 20.00 lbs (9.1 kg)

 Buoyancy
 119.93 lbs (54.4 kg)

 Master Pack Weight
 25.55 lbs (11.6 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Military yes

ACCESSORIES



1609 Lid Organizer



1611 5 pc. Replacement Foam Set



1615 Padded Divider Set



1623 Replacement O-ring



1610EUTP TrekPak Case Divider Kit



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 11-05-25