



## 1450EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### CONFIGURATIONS



**1450EU**  
Standard



**1450NF**  
No Foam



**1450WF**  
With Foam



**1454**  
With Padded Dividers

### DIMENSIONS

<b>Interior (L×W×D)</b>	14.72 x 10.22" x 6.08 (37.4 x 26 x 15.4 cm)
<b>Exterior (L×W×D)</b>	16.10 x 13.03" x 6.88 (40.9 x 33.1 x 17.5 cm)
<b>Lid Depth</b>	1.75" (4.4 cm)
<b>Bottom Depth</b>	4.37" (11.1 cm)
<b>Total Depth</b>	6.12" (15.5 cm)
<b>Int Volume</b>	0.53 ft³ (0.015 m³)
<b>Padlock Hole Diameter</b>	5/16" (12.7 cm)

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane

**Purge Body**  
**Purge Vent**

ABS  
3 Micron Hydrophobic Non-Woven

COLOURS

Black  
Silver

Desert Tan  
Yellow

Orange

OD Green

WEIGHT

**Weight With Foam** 6.39 lbs (2.9 kg)  
**Weight Empty** 5.51 lbs (2.5 kg)  
**Buoyancy** 30.00 lbs (13.6 kg)

TEMPERATURE

**Minimum Temperature** -40°F (-40 °C)  
**Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

**IP67**  
**MIL C-4150J**  
**Def Stan 81-41**

OTHER

**Master Pack** 4  
**Nameplate** yes  
**Military** yes

ACCESSORIES



**1451**  
3 pc. Replacement Foam Set



**1453**  
Replacement O-ring



**1455**  
Padded Divider Set



**1450PF**  
Special Application Panel  
Frame




**1450TPKIT**  
TrekPak Case Divider Kit



**1507**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 07-29-25*