

BL9053-1035AC

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

- Profilierte, ineinandergreifende, abdichtende Trennfugen für Spritzschutz und dichte Versiegelung selbst nach einem Aufprall
- Verstärkte Ecken und Kanten für zusätzlichen Aufprallschutz
- Eingegossene Rippen und Sicken für sicheres, rutschfestes und stabiles Stapeln und zusätzlichen Schutz
- Ausgesparte Beschläge für zusätzlichen Schutz
- Positiver Verriegelungsmechanismus verhindert ein Abreißen des Deckels nach Aufprall und reduziert die Belastung der Beschläge
- Patentierte eingegossene Metalleinlagen für Verschluss/-Scharnierbefestigungspunkte bietet Stabilität
- Aus leichtem, schlagfesten Polyethylen aus einem Guss hergestellt



GRÖSSE

INNERE 90.00 x 53.00" x 45.50 (228.6 x 134.6 x 115.6 cm) **AUSSEN** 94.00 x 57.00" x 50.00 (238.8 x 144.8 x 127 cm)

 Deckeltiefe
 35.25" (89.5 cm)

 Bodentiefe
 10.25" (26 cm)

 Gesamttiefe
 45.5" (115.6 cm)

 Innenvolumen
 125.6 ft³ (3.557 m³)

MATERIALEN

GehäuseRotoMolded PolyethyleneVerschlussSteel (Nickel-black Plated)

O-Ring Dichtung Silicone Sponge

Schaumstoff No Foam, empty case standard

Optional PE and PU, 1 and 2 lb. options filled and lined

Ausgleichsschraube Aluminum

Handgriff Heavy Duty Injection Molded Standard

Beschläge Yellow Carbon Steel Standard

FARBEN

Gray - 133 Fed Std 26270

GEWICHT

 Gewicht
 278.00 lbs (126.1 kg)

 Schwimmfähigkeit
 9401.23 lbs (4264.3 kg)

 Master Pack Weight
 280.00 lbs (127 kg)

TEMPERATUR

min. Temperatur -20°F (-28.9 °C)

max. Temperatur 140°F (60 °C)

ANDERE

Militär ja

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 12-18-25