



## 2010Z0 SabreLite™

The SabreLite™ 2010Z0 LED is Peli's flagship LED torch. The rugged, light weight anti-static PC/PBT resin body is submersible to 1 meter for 30 mins (IPX7) and a twist on/off lens shroud eliminates accidental discharge. It is powered by 3 C alkaline cells. The SabreLite™ 2010Z0 is the future of LEDs. Certified to ATEX Zone 20.




### DIMENSIONS

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 8.11" (20.6 cm) |
|---------------|-----------------|

### MATERIALS

|                                |                                    |
|--------------------------------|------------------------------------|
| <b>Body</b>                    | Anti-static PC/PBT                 |
| <b>O-Ring</b>                  | Ethylene Propylene                 |
| <b>Lens</b>                    | Anti-static PMMA                   |
| <b>Shroud</b>                  | Anti-static Impact Modified PC/PBT |
| <b>Clip</b>                    | Anti-static Impact Modified PC/PBT |
| <b>Contact Spring Retainer</b> | Stainless Steel / Brass Nickel     |

### COLOURS

|  |
|--|
|  High Visibility Yellow |
|--|

### LIGHT SPECS

|                  |     |
|------------------|-----|
| <b>Lamp Type</b> | LED |
|------------------|-----|

### POWER

|                         |          |
|-------------------------|----------|
| <b>Battery Size</b>     | C        |
| <b>Battery Type</b>     | Alkaline |
| <b>Battery Quantity</b> | 3        |
| <b>Volts</b>            | 4.5v     |

### WEIGHT

|                                 |                  |
|---------------------------------|------------------|
| <b>Weight With Batteries</b>    | 13.4 oz (380 gr) |
| <b>Weight Without Batteries</b> | 5.4 oz (153 gr)  |

### SWITCH






|                    |                      |
|--------------------|----------------------|
| <b>Switch Type</b> | Twisting Lens Shroud |
| <b>Light Modes</b> | On / Off             |

CERTIFICATIONS

ATEX Zone 0

OTHER

|              |     |
|--------------|-----|
| Submersible  | yes |
| Minimum Pack | 1   |
| Package Code | C   |

| FL1 STANDARD  | HIGH          |
|---|---------------|
|    | 129<br>LUMENS |
|    | 22h 0mins     |
|   | 135m          |
|  | 4582cd        |
|  | IPX7          |