

# 0450 Protector Mobile Tool Chest

We took our toughest mobile tool chest and made it tougher. Now featuring an aluminum rail slide system, each tray slides out into a secure position for easy access of your tools and can be effortlessly removed for repositioning or cleaning.

The robust design has been tested for water submersion, extreme temperatures, and drop tested from 5 feet. This case can take a beating while keeping your tools intact. Plus, the extendable trolley handle and rough terrain wheels take the strain off of transport.

- Auto pressure equalization valves
- Two way handles
- Generation 2
- Aluminum rail slide system
- Removable drawers
- Extended length trolley handle
- Field replaceable wheels
- Metal butterfly compression latches
- Stable, wide track mobility
- Heavy duty butress hinges
- \* Tools not included
- 2 versions available: with 6 (4 shallow drawers and 2 deep drawers) or 7
- (6 shallow drawers and 1 deep drawer) removable tool drawers

# CONFIGURATIONS



**0450** Standard



0450SD4 4 Shallow / 2 Deep Drawers



0450SD6 6 Shallow / 1 Deep Drawers

#### DIMENSIONS

| Interior (L×W×D)      | 20.56 x 10.97" x 12.65 (52.2 x 27.9 x 32.1 cm) |
|-----------------------|--|
| Exterior (L×W×D)      | 23.95 x 14.75" x 17.95 (60.8 x 37.5 x 45.6 cm) |
| Int Volume            | 1.65 ft <sup>3</sup> (0.047 m <sup>3</sup> )   |
| Padlock Hole Diameter | 0.31" (0.8 cm)                                 |

#### MATERIALS

| Body       | Polypropylene                  |
|------------|--------------------------------|
| Latch      | ABS                            |
| O-Ring     | Polymer                        |
| Pins       | Stainless Steel                |
| Purge Body | ABS                            |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

# COLOURS

#### Black

# WEIGHT

Weight With Drawers 48.40 lbs (22 kg) and Tray

### TEMPERATURE

Minimum Temperature-40°F (-40 °C)Maximum Temperature190°F (87.8 °C)

## ACCESSORIES





**0450DDK** Deep Drawer Kit



**0450TT** Top Tray

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 07-28-25