



# 1490

## Protector

Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Double safety locking latches with keys**
- **Fits notebook computers up to 17.3" L x 11.0" W x 3.3" D (43.94 x 27.94 x 8.38 cm)**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### CONFIGURATIONS



**1490**  
Standard



**1490NF**  
No Foam



**1490WF**  
With Foam

### DIMENSIONS

|                              |   |
|------------------------------|---|
| <b>Interior (LxWxD)</b>      | 17.75 x 11.37" x 4.12 (45.1 x 28.9 x 10.5 cm) |
| <b>Exterior (LxWxD)</b>      | 19.87 x 13.93" x 4.68 (50.5 x 35.4 x 11.9 cm) |
| <b>Lid Depth</b>             | 1.50" (3.8 cm)                                |
| <b>Bottom Depth</b>          | 2.62" (6.7 cm)                                |
| <b>Total Depth</b>           | 4.12" (10.5 cm)                               |
| <b>Int Volume</b>            | 0.48 ft <sup>3</sup> (0.014 m <sup>3</sup> )  |
| <b>Padlock Hole Diameter</b> | 0.25" (0.6 cm)                                |

### MATERIALS

|                   |                     |
|-------------------|---------------------|
| <b>Body</b>       | ABS                 |
| <b>Latch</b>      | ABS                 |
| <b>O-Ring</b>     | Polymer             |
| <b>Pins</b>       | Stainless Steel     |
| <b>Foam</b>       | 1.3 lb Polyurethane |
| <b>Purge Body</b> | ABS                 |

**Purge Vent**

3 Micron Hydrophobic Non-Woven

**COLOURS**

■ Black

**WEIGHT**

|                           |                      |
|---------------------------|----------------------|
| <b>Weight With Foam</b>   | 6.50 lbs (2.95 kg)   |
| <b>Weight Empty</b>       | 5.47 lbs (2.48 kg)   |
| <b>Buoyancy</b>           | 41.00 lbs (18.6 kg)  |
| <b>Master Pack Weight</b> | 27.30 lbs (12.38 kg) |

**TEMPERATURE**

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 190°F (87.8 °C) |

**CERTIFICATIONS****Def Stan 81-41****OTHER**

|                    |     |
|--------------------|-----|
| <b>Master Pack</b> | 4   |
| <b>Nameplate</b>   | yes |
| <b>Military</b>    | yes |

**ACCESSORIES**

**1472**  
Shoulder Strap



**1491**  
3 pc. Replacement Foam Set



**1493**  
Replacement O-ring



**1498**  
Computer Lid Organizer



**1490PF**  
Special Application Panel Frame



**1499C**  
Computer Bottom Insert



**1507QM**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 06-19-26