

1450EU

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

· Watertight, crushproof, and dustproof

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1450EU Standard



1450NF No Foam



1450WF With Foam



1454With Padded Dividers

DIMENSIONS

 Interior (L×W×D)
 14.72 x 10.22" x 6.08 (37.4 x 26 x 15.4 cm)

 Exterior (L×W×D)
 16.10 x 13.03" x 6.88 (40.9 x 33.1 x 17.5 cm)

 Lid Depth
 1.75" (4.4 cm)

 Bottom Depth
 4.37" (11.1 cm)

 Total Depth
 6.12" (15.5 cm)

 Int Volume
 0.53 ft³ (0.015 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 6.39 lbs (2.9 kg)

 Weight Empty
 5.51 lbs (2.5 kg)

 Buoyancy
 30.00 lbs (13.6 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41

OTHER

Master Pack4NameplateyesMilitaryyes

ACCESSORIES



1451 3 pc. Replacement Foam Set



1453 Replacement O-ring



1455 Padded Divider Set



1450PFSpecial Application Panel Frame



1450TPKIT TrekPak Case Divider Kit



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Document created on 05-09-24