



# SMAC2112-02/29/05W

## SuperMAC™

5U

Peli™ SuperMAC™ rackmount cases are ideal for field-deployed equipment and sheltered applications. Typical uses include control consoles and panels, radar and microwave antennas, solid-state circuit electronics, or radio, TV and communications equipment.

- A space-saving, lightweight case with a removable rack option
- Protection for equipment from 20-200 lbs
- Equipment typically will have 40-70 G fragility
- Available in either threaded aluminum frame or a square hole frame up to 14U and 340 lbs



### DIMENSIONS

|                                |  |
|--------------------------------|--|
| <b>Exterior (LxWxD)</b>        | 38.50 x 23.80" x 14.90 (97.8 x 60.5 x 37.8 cm) |
| <b>Rack Depth</b>              | 24.00" (61 cm)                                 |
| <b>Interior Lid Depth</b>      | 2.20" (5.6 cm)                                 |
| <b>Interior Back Lid Depth</b> | 5.20" (13.2 cm)                                |

### MATERIALS

### COLOURS

|                              |                                  |                             |                             |
|------------------------------|----------------------------------|-----------------------------|-----------------------------|
| ■ Black - 032 Fed Std 27040  | ■ Olive Drab - 137 Fed Std 34096 | ■ Tan - 250 Fed Std 20372   | ■ Red - 130 Fed Std 21105   |
| ■ Blue - 135 Pantone 292U    | ■ White - 132 Fed Std 27925      | ■ Yellow - 136 Pantone 012U | ■ Green - 138 Fed Std 24052 |
| ■ Orange - 134 Fed Std 12197 | ■ Yellow - 131 Fed Std 23538     | ■ Maroon - 197 Pantone 202U | ■ Blue - 101 Fed Std 25052  |
| ■ Purple - 129 Pantone 245U  |                                  |                             |                             |

### WEIGHT

|               |                      |
|---------------|----------------------|
| <b>Weight</b> | 55.00 lbs (24.95 kg) |
|---------------|----------------------|

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 04-25-26