



## iM2075 Storm

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



### CONFIGURATIONS



### DIMENSIONS

<b>Interior (L×W×D)</b>	9.50 x 7.50" x 7.25 (24.1 x 19.1 x 18.4 cm)
<b>Exterior (L×W×D)</b>	11.80 x 9.80" x 7.70 (30 x 24.9 x 19.6 cm)
<b>Lid Depth</b>	1.50" (3.8 cm)
<b>Bottom Depth</b>	5.75" (14.6 cm)
<b>Total Depth</b>	7.25" (18.4 cm)
<b>Int Volume</b>	0.3 ft <sup>3</sup> (0.008 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.28" (0.7 cm)

### MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>Purge Vent</b>	Gortex membrane

### COLOURS

- Black      ■ OD Green      ■ Yellow

## WEIGHT

---

<b>Weight With Foam</b>	3.70 lbs (1.68 kg)
<b>Weight Empty</b>	3.30 lbs (1.5 kg)
<b>Buoyancy</b>	18.20 lbs (8.26 kg)
<b>Master Pack Weight</b>	18.20 lbs (8.26 kg)

## TEMPERATURE

---

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

## CERTIFICATIONS

---

**IP67**

## OTHER

---

<b>Master Pack</b>	4
<b>Military</b>	yes

## ACCESSORIES

---



**iM2075-FOAM**  
4 pc. Replacement Foam Set



**iM-STRAP-S-VER2**  
Padded Shoulder Strap



**iM-LIDSTAY**  
Lid Stay



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**iM20XX-M4-BEZEL**  
Base Bezel Kit (Metric)

---

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 05-06-26