



## 1300 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### CONFIGURATIONS



**1300**  
Standard



**1300NF**  
No Foam



**1300WF**  
With Foam

### DIMENSIONS

<b>Interior (L×W×D)</b>	9.17 x 7.00" x 6.12 (23.3 x 17.8 x 15.5 cm)
<b>Exterior (L×W×D)</b>	10.62 x 9.68" x 6.87 (27 x 24.6 x 17.4 cm)
<b>Lid Depth</b>	1.18" (3 cm)
<b>Bottom Depth</b>	4.93" (12.5 cm)
<b>Total Depth</b>	6.11" (15.5 cm)
<b>Int Volume</b>	0.23 ft <sup>3</sup> (0.007 m <sup>3</sup> )

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

COLOURS

 Black	 Orange	 Silver	 Yellow
---	--	--	--

WEIGHT

<b>Weight With Foam</b>	3.53 lbs (1.6 kg)
<b>Weight Empty</b>	3.09 lbs (1.4 kg)
<b>Buoyancy</b>	12.35 lbs (5.6 kg)
<b>Master Pack Weight</b>	16.85 lbs (7.6 kg)

TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	190°F (87.8 °C)







CERTIFICATIONS

<b>IP67</b>	
<b>Def Stan 81-41</b>	

OTHER

<b>Master Pack</b>	4
<b>Military</b>	yes

ACCESSORIES

				
<b>1203</b> Replacement O-ring	<b>1301</b> 4 pc. Replacement Foam Set	<b>1200PF</b> Special Application Panel Frame	<b>1507</b> Quick Mounts - set of 4	<b>1506TSA</b> TSA Lock
				
<b>1500D</b> Desiccant Silica Gel				