

# 1780

## Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- 4 strong polyurethane wheels with stainless steel bearings
- The new class of XXL Peli Transport Cases
- Watertight, crushproof, and dustproof
- 50/50 lid-to-base ratio for easy loading
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Completely detachable lid for full access
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



## **CONFIGURATIONS**



**1780** Standard



**1780NF** No Foam



1780WF With Foam

#### **DIMENSIONS**

Interior (L×W×D) 41.12 x 21.54" x 14.88 (104.4 x 54.7 x 37.8 cm) Exterior (L×W×D) 44.90 x 25.32" x 16.50 (114 x 64.3 x 41.9 cm)

 Lid Depth
 7.58" (19.3 cm)

 Bottom Depth
 7.30" (18.5 cm)

 Total Depth
 14.88" (37.8 cm)

 Int Volume
 7.63 ft³ (0.216 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

#### **MATERIALS**

**Body** Polypropylene

Latch EXL O-Ring Polymer

PinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

#### **COLOURS**



## WEIGHT

 Weight With Foam
 49.00 lbs (22.2 kg)

 Weight Empty
 38.40 lbs (17.4 kg)

 Buoyancy
 500.00 lbs (226.8 kg)

 Master Pack Weight
 56.00 lbs (25.4 kg)

#### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

## **CERTIFICATIONS**

Def Stan 81-41

## OTHER

Wheels 4
Master Pack 1
Nameplate yes

## **ACCESSORIES**



**1781** 6 pc. Replacement Foam Set



1783 Replacement O-ring



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 05-11-24