



1170 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **The hand-held electronics protection solution**
- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Easy open Double Throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1170
Standard



1170NF
No Foam



1170WF
With Foam

DIMENSIONS

Interior (L x W x D)	10.54 x 6.04" x 3.16 (26.8 x 15.3 x 8 cm)
Exterior (L x W x D)	11.64 x 8.34" x 3.78 (29.6 x 21.2 x 9.6 cm)
Lid Depth	1.08" (2.7 cm)
Bottom Depth	2.08" (5.3 cm)
Total Depth	3.16" (8 cm)
Int Volume	0.12 ft³ (0.003 m³)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black	Silver	Orange	Yellow
-------	--------	--------	--------

WEIGHT

Weight With Foam	2.10 lbs (1 kg)
-------------------------	-----------------

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

Weight Empty 1.96 lbs (0.9 kg) info@peli.com • www.peli.com
Buoyancy 7.25 lbs (3.3 kg)
Master Pack Weight 12.79 lbs (5.8 kg) *Document created on 06-20-19*

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP67

FOAM PROPERTIES

Layer 1 (Lid) 1.10" Convolute
Layer 2 (Base) 0.50" Pad
Layer 3 (Base) 1.50" Pick N Pluck

OTHER

Master Pack 6

ACCESSORIES