



# 0370

## Protector

Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Large 2-person fold down handles**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### CONFIGURATIONS



**0370**  
Standard



**0374**  
With Padded Dividers



**0370NF**  
No Foam



**0370WF**  
With Foam

### DIMENSIONS

<b>Interior (L x W x D)</b>	24.00 x 24.00" x 24.00 (61 x 61 x 61 cm)
<b>Exterior (L x W x D)</b>	26.50 x 26.50" x 25.25 (67.3 x 67.3 x 64.1 cm)
<b>Lid Depth</b>	5.00" (12.7 cm)
<b>Bottom Depth</b>	19.00" (48.3 cm)
<b>Total Depth</b>	24" (61 cm)
<b>Int Volume</b>	8 ft <sup>3</sup> (0.227 m <sup>3</sup> )

### MATERIALS

<b>Body</b>	Polypropylene
<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

### COLOURS

- Black

### WEIGHT

<b>Weight With Foam</b>	41.00 lbs (18.6 kg)
-------------------------	---------------------

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

**Weight Empty** 31.97 lbs (14.5 kg) [info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)  
**Buoyancy** 465.18 lbs (211 kg)  
**Master Pack Weight** 46.78 lbs (21.2 kg) *Document created on 06-26-19*

TEMPERATURE

**Minimum Temperature** -40°F (-40 °C)  
**Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67  
Def Stan 81-41  
STANAG 4280

FOAM PROPERTIES

**Layer 1 (Lid)** 1.90" Pad  
**Layer 2 (Lid)** 2.00" Convolute  
**Layer 3 (Base)** 1.00" Pad  
**Layer 4 (Base)** 1.00" Pad  
**Layer 5 (Base)** 4.13" Pick N Pluck  
**Layer 6 (Base)** 4.13" Pick N Pluck  
**Layer 7 (Base)** 4.13" Pick N Pluck  
**Layer 8 (Base)** 4.13" Pick N Pluck

OTHER

**Master Pack** 1  
**Nameplate** yes  
**Reduced Area** yes  
**Military** yes

---

ACCESSORIES