



1150 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1150
Standard



1150NF
No Foam



1150WF
With Foam

DIMENSIONS

Interior (L x W x D)	8.29 x 5.79" x 3.75 (21.1 x 14.7 x 9.5 cm)
Exterior (L x W x D)	9.44 x 7.80" x 4.29 (24 x 19.8 x 10.9 cm)
Lid Depth	0.75" (1.9 cm)
Bottom Depth	2.87" (7.3 cm)
Total Depth	3.62" (9.2 cm)
Int Volume	0.1 ft³ (0.003 m³)

MATERIALS

Body	Polypropylene
Latch	Polypropylene
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Black	 Silver	 Yellow
---	---	---

WEIGHT

Weight With Foam	1.75 lbs (0.8 kg)
Weight Empty	1.61 lbs (0.7 kg)
Buoyancy	8.00 lbs (3.6 kg)

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

Master Pack Weight 13.95 lbs (6.3 kg) info@peli.com • www.peli.com

TEMPERATURE

Minimum Temperature -40°F (-40 °C)

Maximum Temperature 210°F (98.9 °C)

Document created on 06-26-19

CERTIFICATIONS

IP67

Def Stan 81-41

STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid) 0.74" Convolute

Layer 2 (Base) 0.50" Pad

Layer 3 (Base) 2.53" Pick N Pluck

OTHER

Master Pack 6

Military yes

ACCESSORIES