



2000Z1 SabreLite™

Same features as the SabreLite™ 2000 with static-dissipation materials body. SabreLite™ 2000Z1 is ATEX certified safe for use in hazardous Zone 1 (Category 2) locations, and is perfect for professionals who work in areas with high risk of explosion such as chemical, pharmaceutical, power, oil and gas, and fire rescue.



DIMENSIONS

Length	7.79" (19.8 cm)
---------------	-----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	Ethylene Propylene
Lens	Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT
Clip	Anti-static Impact Modified PC/PBT
Contact Spring Retainer	Stainless Steel

COLOURS

 Gray
--

LIGHT SPECS

Lamp Type	Incandescent (Xenon)
------------------	----------------------

POWER

Battery Size	C
Battery Type	Alkaline
Battery Quantity	3
Volts	4.5v

WEIGHT

Weight With Batteries	12.8 oz (363 gr)
Weight Without Batteries	5.3 oz (150 gr)

SWITCH

Switch Type	Twisting Lens Shroud
Light Modes	On / Off

CERTIFICATIONS

ATEX Zone 1

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

OTHER






Minimum Pack

6

Package Code

C

Document created on 04-26-24

FL1 STANDARD	HIGH
	39 LUMENS
	6h 0mins
	177m
	7852cd
	IPX7

ACCESSORIES